



# JETT SINGLEPOINT

Electric Instantaneous Water Heater

**Jett Instantaneous Singlepoint Water Heater** is Asia's First Immersed Thermostat System. Built to achieve the best performance on accuracy, safety and faster thermal sensing

### INNOVATIONS:

- Electronic Variable Temperature Control
- Thermal Cut-off (Anti-Scalding), Faster Sensing
- Suitable for high and low water pressure area
- Minimum activating pressure at only 1.5 psi
- Splash proof
- Built-in ELCB

## TECHNICAL AND SPECIFICATION INFORMATIONS

MODEL	JETT SINGLEPOINT
TECHNOLOGY	Electronic Control System
OPERATION/FEATURES	Fully Automatic Operation / Built-in ELCB
APPLICATION	Point of Use (Shower)
TEMPERATURE SELECTOR & CONTROL	Step-less (minimum to maximum)
ACTIVATING MECHANISM	Flow Sensor Activated Power Switch
THERMAL/OVER-TEMPERATURE CUT-OFF	50-55°C; Final Cut OFF ± 80°C
ELECTRICAL POWER RATING	3.5 Kilowatts
VOLTAGE/ CYCLE / PHASE	220 - 240 VAC / 50 - 60 Hz / Single Phase
REQUIRED CIRCUIT BREAKER RATING	30 Amperes
CABLE SIZE	#12
MINIMUM ACTIVATING PRESSURE	1.5 psi (pounds per square inch)
OPERATING WATER PRESSURE	0.3-3.4 BAR (5-50 PSI)
WATER CONNECTION	1/2 " / 15 mm
DIMENSIONS (mm)	356 (H) X 246 (W) X 116 (D)
WEIGHT (Kg)	3
ACCESSORIES	Teleshower Set / fittings
MANUFACTURER	Maxvic Sdn. Bhd.
MADE	Malaysia
QUALITY APPROVAL	UL / CSA